

SAFETY DATA SHEET

Section 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Product Name: BM-6400 Ethanol Disinfectant

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use(s): Disinfectant

Details of the supplier of the safety data sheet

| | | | |
|---------------------------|--|---|--|
| Manufacturer: | N.A.K.P Foto Inc. 2575 De Miniac Ville Saint Laurent, Quebec H4S 1E5 Canada | Distributor: | B.M. Group Inc. 5890 Monkland Avenue, Suite 16 Montreal Quebec H4A 1G2 Canada |
| Website: | www.nakpfoto.com | Website : | http://www.bmcanada.ca |
| Email: | paul@nakpfoto.com | Email: | info@bmcanada.ca |
| Tel (514) 932-8057 | | Tel: (514) 738-5200 Toll Free 1-800-561-9818 | |
| Fax (514) 932-8057 | | Fax: (514) 738-2290 | |

Emergency telephone number

Emergency contact: 1-800-463-5060 Poison Control Center in Quebec, Canada

Canutec: 613-996-6666

Notes:

This product is registered with Health Canada as a disinfectant. While this product is generally safe and effective during normal use as per directions on label and as per guidelines in this SDS, this SDS also contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions, large production plants as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product.

Section 2. Hazards identification

Classification of the substance or mixture

GHS Classification for mixture:

Specific target organ toxicity - single exposure - Category 3 (Narcotic)
Hazardous to the aquatic environment, short-term (Acute) - Category 3
Specific target organ toxicity - single exposure - Category 3 (Respiratory)
Specific target organ toxicity - single exposure - Category 2
Serious eye irritation - Category 2
Skin irritation - Category 2
Acute Toxicity Oral - Category 4
Flammable Liquids - Category 2

Label elements

Pictograms:



Signal Words:

Danger

Hazard Statements: Read the label before using. Keep out of reach of children.

Highly flammable liquid and vapour.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs. Route(s) of exposure: Unknown. Affected organ(s): Unknown.

Harmful to aquatic life.

Precautionary Statements:**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Keep cool.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating, lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Do not breathe vapors, spray.

Avoid breathing vapors, spray.

Wash your hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves, eye protection, protective clothing, face protection.

FIRST AID TREATMENT: If exposed or concerned: Call a POISON CENTER, doctor if you feel unwell. IF SWALLOWED: Call a POISON CENTER, doctor if you feel unwell. Rinse mouth. IF IN EYES: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Wash with plenty of water. Rinse skin with water or shower. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation persists: Get medical advice. In case of fire: Use dry chemical, water spray, carbon dioxide, or alcohol-resistant foam to extinguish.

Storage

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of the empty container in accordance with municipal/provincial/territorial requirements. Offer for recycling, if available.

| |
|--|
| Section 3. Composition/information on ingredients |
|--|

Substances

No available data for this section.

Mixtures

| Identifiers | Ingredients | Percentage | Classification |
|-------------|-------------|------------|----------------|
| 64-17-5 | Ethanol | 71% | |
| 67-56-1 | Methanol | 9% | |

| Identifiers | Ingredients | Percentage | Classification |
|-------------|----------------|------------|----------------|
| 141-78-6 | Ethyl acetate | 0.4% | |
| 90-43-7 | O-Phenylphenol | 0.29% | |

Section 4. First-Aid Measures

Description of First Aid Measures

In the event of splashes or contact with eyes

Hold eyelids open to ensure adequate flushing. Seek medical attention if irritation, redness, or any other symptom develops. Immediately flush with clean, low-pressure water for several minutes.

In the event of splashes or contact with skin

Wash contaminated areas thoroughly with water. If redness or other symptoms occur, seek medical advice / attention.

In the event of ingestion

In case of ingestion of large quantities immediately take the exposed person to hospital. Rinse mouth with water. Call a poison center, a doctor, or medical service. DO NOT INDUCE VOMITING.

In the event of inhalation

Remove person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if symptoms occur.

Most important symptoms and effects, both acute and delayed

No available data for this section.

Indication of any immediate medical attention and special treatment needed

No available data for this section.

Section 5. Firefighting Measures

Extinguishing media

Suitable Extinguishing Media

For large fires: Water spray. Fog. Alcohol-resistant foam. Use water spray to cool fire-exposed containers.

For small fires: Dry chemical. Water spray. Carbon dioxide. Alcohol-resistant foam.

Unsuitable Extinguishing Media

Straight streams of water. Water (may be ineffective).

Special hazards arising from the substance or mixture

Specific Hazards Arising from Combustion of Products

INDIRECT FIRE HAZARDS: May be ignited by sparks. Gas/vapour spreads at floor level.

DIRECT FIRE HAZARDS: Highly Flammable. Gas/vapour flammable with air within explosion limits.

Fire / decomposition hazards: Toxic gases.

Combustion Products

Carbon dioxide (CO₂). Carbon monoxide (CO).

Advice for firefighters

Protective Measures for Fire-Fighting

Wear full protective clothing.

Special Protective Actions for Fire-Fighters

Do not scatter the product. Evacuate the people from the area. Dispose off fire control water later. Move containers from the fire area if it is possible to do so without risk to personnel. Use water spray or fog; do not use straight streams.

Other Information for Fire Fighters

No available data for this section.

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Eliminate all sources of heat and ignition. Wear protective gloves, clothing, and protective goggles to prevent contact with skin and eyes.

Environmental precautions

Prevent contamination of soil and surface water.

Methods and material for containment and cleaning up

Absorb with earth, sand, or other non-combustible material.

Reference to other sections

No available data for this section.

Section 7. Handling and Storage

Precautions for safe handling

No smoking or open flame in storage, use, or handling areas. Wear protective gloves, clothing, and protective goggles to prevent contact with skin and eyes.

Conditions for safe storage, including any incompatibilities

Conditions for Safe Storage

Keep away from: Direct sunlight. Heat. Open flame. Sparks.

Keep container tightly closed. Store in a cool, dry, well-ventilated area away from incompatible substances (See section 10).

Suitable Packaging

Compatible container / packaging material: Aluminum. Copper. Glass containers. Iron. Nickel. Polyethylene. Polypropylene. Stainless steel 304.

Incompatible Materials

No available data for this section.

Specific end use(s)

No available data for this section.

Section 8. Exposure Controls / Personal Protection

Control parameters

Control Parameters / Limits for Product

No available data for this section.

Control Parameters / Limits for Component

Ethanol

| | |
|--|---------------------------------------|
| OSHA PEL (TWA) | 1000 ppm. 1900 mg/m ³ . |
| ACGIH STEL (TLV) | 1000 ppm. 1880 mg/m ³ . |
| Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants (TWA-EV) | 1000 ppm. 1880 mg/m ³ . |
| Ethyl acetate | |
| WEL-STEL | 400 ppm. |
| DNEL Consumers, Inhalation, Long-term local effects | 367 mg/m ³ . |
| DNEL Consumer, Oral, Long term, systemic effects | 4.5 mg/kg. |
| DNEL Workers, Inhalation, Short-term, local effects | 1468 mg/m ³ . |
| DNEL Workers, Inhalation, Short term, systemic effects | DNEL 1468 mg/m ³ . |
| DNEL Consumers, Inhalation, Acute systemic effects | 734 mg/m ³ . |
| DNEL Consumers, Inhalation, Acute local effects | 734 mg/m ³ . |
| DNEL Consumers, Inhalation, Long-term systemic effects | 367 mg/m ³ . |
| DNEL Workers, Inhalation, Long-term systemic effects | 734 mg/m ³ . |
| DNEL Workers, Inhalation, Long-term local effects | 734 mg/m ³ . |
| DNEL Consumers, Skin contact, Long-term systemic effects | 37 mg/kg. |
| DNEL Workers, Skin contact, Long-term systemic effects | 63 mg/kg. |

Methanol

| | |
|-------------|--|
| STEL | 328 mg/m ³ OEL, Canada, Alberta 250 ppm OEL, Canada, Alberta |
| TWA | 262 mg/m ³ Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants (TWAEV) 200 ppm Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants (TWAEV) 262 mg/m ³ OEL, Canada, Alberta 200 ppm OEL, Canada, Alberta |

Exposure controls

Engineering Measures

In large plants or industrial production areas, ensure that there is sufficient ventilation of the area. Eye wash stations are recommended in areas where product is stored in large quantities. Provide adequate general and local exhaust ventilation.

Respiratory Protection

In large plants or industrial production areas, certified self-contained breathing apparatus must be available in case of emergency.

Eye/Face Protection

In large plants or industrial production areas, wear chemical goggles and face shield. Remove contact lenses. In industrial plants or large production areas, ensure eye-wash stations are available. For use in small settings or offices wear a face shield, and a procedure and training for washing eyes in a sink is recommended.

Skin and Body Protection

In large plants or industrial production areas, wear protective gloves and flame retardant antistatic protective clothing.

Hand Protection

Ensure gloves are certified. Wear impermeable gloves.

Hygiene Measures

No available data for this section.

Environmental exposure controls

No available data for this section.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

| | |
|---------------------------|------------------------------------|
| Physical State | Liquid |
| Appearance | Not available |
| Odor | Characteristic odor |
| Odor threshold | Not available |
| pH | 7 to 7.5 |
| Melting point | Not available |
| Boiling point | 77.8°C / 172.04°F |
| Flash Point | 20°C / 68°F ASTMD92 |
| Evaporation rate | 2.7 multiplier w/r/t butyl acetate |
| Flammability | Liquid Highly Flammable |
| Flammability limit | 3.3 to 19 %vol |
| Vapor pressure | 50 mmHg |
| Vapor density | 1.59 g/cm ³ |

| | |
|------------------------------|------------------------------|
| Relative density | 0.825 multiplier w/r/t water |
| Solubility | Very soluble |
| Solubility in other solvents | Not available |
| Partition coefficient | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | Not available |
| Freezing point | Not available |
| Percent volatiles | 100 %vol |
| Explosion limit (upper) | 3.3 %vol |
| Explosion limit (lower) | 19 %vol |

Other Information

No available data for this section.

Section 10. Chemical Stability & Reactivity Information

Reactivity

Chemical stability: This product is stable under ambient condition.

Chemical Stability

No available data for this section.

Possibility of Hazardous Reactions

Dangerous reactions are not expected if the technical instructions in storage of chemicals are met.

Conditions to Avoid

Keep away from: Direct sunlight. Electrical equipment. Fire. Heat. Open flame. Sparks. Static electricity.

Incompatible Materials

Avoid contact or storage with: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products

Decomposition will Result in Production of: Carbon dioxide (CO₂). Carbon monoxide (CO).

Section 11. Toxicological Information

Information on toxicological effects

Toxicological Information for Product

No available data for this section.

Toxicological Information for Component

Ethanol

LC50 Inhalation - Not Specified 39 g/m³ (4h), Mouse.
20000 ppmV (10h), Rat.

LD50 Oral 3450 mg/kg Mouse.
6300 mg/kg Rabbit.
7060 to 9000 mg/kg Rat.

Ethyl acetate

| | |
|--|---------------------------------|
| LC50 Inhalation - Not Specified | Greater than 28.6 mg/l (4h). |
| LD50 Dermal | Lesser than 18000 mg/kg Rabbit. |
| LD50 Oral | 5620 mg/kg Rat. |

Methanol

| | |
|--|---|
| LC50 Inhalation - Not Specified | 83.2 mg/l (4h), Rat. 64000 ppmV (4h), Rat. |
| LD50 Dermal | 15800 mg/kg Rabbit. |
| LD50 Oral | 5628 mg/kg Rat. |

O-Phenylphenol

| | |
|------------------|-----------------|
| LD50 Oral | 2733 mg/kg Rat. |
|------------------|-----------------|

Irritation/Corrosion Information for Product

No available data for this section.

Irritation/Corrosion Information for Component

O-Phenylphenol

Eyes: Severe eye irritation, Rabbit.
Skin: Irritating to skin, Rabbit - OECD Test Guidelines 404.

Ethyl acetate

Eye contact: Causes eye irritation.
Skin contact: 24h, Rabbit, May cause skin dryness or cracking.

Ethanol

Draize Test - Eye: 500 mg, Rabbit, Severe. 500 mg(24h), Rabbit, Mild.
Draize Test - Skin: 20 mg(24h), Rabbit, Moderate.

| |
|---|
| Section 12. Ecological Information |
|---|

Toxicity**Ecotoxicity Values for Product**

No available data for this section.

Ecotoxicity Values for Component

Ethanol

| | |
|---------------------------|--|
| EC50 | 34900 mg/l (5-30min), Phytobacterium phosphoreum. |
| LC50 Environmental | Greater than 10000 mg/l. 12900 to 15300 mg/l (96h), Rainbow Trout. 11200 mg/l (24h), Rainbow Trout. 9000 mg/l (24h). Greater than 7800 mg/l Daphnia. |

Ethyl acetate

| | |
|---------------------------|---|
| EC50 | 610 mg/l (48h) Crustacians: Daphnia magna. 5600 mg/l (48h) Algae: Pseudokirch neriella subcapitata. 3300 mg/l (48h) Algae: Scenedesmus subspicatus. |
| LC50 Environmental | 230 mg/l (96h) Fish: Pimephales promelas. |

Methanol

| | |
|-------------|--|
| EC50 | 43000 mg/l (5min), Phytobacterium phosphoreum. 40000 mg/l (15min), Phytobacterium phosphoreum. 39000 mg/l (25min), Phytobacterium phosphoreum. |
|-------------|--|

LC50 Environmental 29400 mg/l (96h), Fish, Fathead Minnow (28 days old).
13 mg/l (96h), Fish, Rainbow Trout (Fingerling).
8000 mg/l (43h), Fish, Trout.

O-Phenylphenol

EC50 0.85 mg/l (72h), Algae.

LC50 Environmental 4.5 mg/l (96h), Fish, Danio rerio (Zebra Fish).
2.7 mg/l (48h), Daphnia magna (water flea).

Persistence and degradability

No available data for this section.

Bioaccumulative potential

Bioaccumulative Potential for Product

No available data for this section.

Bioaccumulative Potential for Component

Ethyl acetate

LogPow: 0.68 (3d), Unlikely.

Mobility in soil

No available data for this section.

Results of PBT and vPvB assessment

No available data for this section.

Other adverse effects

No available data for this section.

Section 13. Disposal Considerations

Waste treatment methods

Waste Disposal Regulation(s) / Operation

Dispose of according to local, state, and federal regulations.

Waste Treatment Methods

No available data for this section.

Section 14. Transportation Information

| | ADR | IMDG | IATA | DOT |
|-----------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---|
| UN number | No available data for this section. | No available data for this section. | No available data for this section. | 1986 |
| UN proper shipping name | No available data for this section. | No available data for this section. | No available data for this section. | ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (Ethanol, Methanol) |
| Transport hazard class(es) | No available data for this section. | No available data for this section. | No available data for this section. | 3 (6.1) |
| Packing group | No available data for this section. | No available data for this section. | No available data for this section. | II |

| | ADR | IMDG | IATA | DOT |
|---|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Environmental hazards | No available data for this section. | No available data for this section. | No available data for this section. | No available data for this section. |
| | | | | |
| Special precautions for user | No available data for this section. | | | |
| Transport in bulk according to Annex II of Marpol and the IBC Code | No available data for this section. | | | |
| Other | Flammable liquid. | | | |

Section 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, Health and Environmental Regulations for Product

No available data for this section.

Safety, Health and Environmental Regulations for Component

Methanol

| | |
|------------------------|---|
| DSL (Canada): | Present. |
| TSCA: | Present. |
| WHMIS (Canada): | B2 - Flammable and combustible material - Flammable Liquid. D1B - Very Toxic Material. D-2A: Toxic material. D2B Toxic Material Causing other Toxic Effects. |

O-Phenylphenol

| | |
|------------------------|--|
| WHMIS (Canada): | D2B Toxic Material Causing other Toxic Effects. Moderate Skin Irritant. |
|------------------------|--|

Ethanol

| | |
|----------------------|----------|
| DSL (Canada): | Present. |
| TSCA: | Present. |

Chemical safety assessment

No available data for this section.

Section 16. Other Information

Disclaimer

The above information is accurate to the best of our knowledge, however since data, safety standards and government regulations change, and the conditions of handling and use or misuse are beyond our control, manufacturer and distributor, above mentioned, make no warranty either expressed or implied with respect to the completeness or continuing accuracy of information herein and disclaims all liability for reliance thereon. Do not use ingredient information and / or ingredient percentages in this SDS as a product specification.

Glossary

ACGIH: American Conference of Governmental Industrial Hygienists.

DOT: Department of Transportation, USA.

LC 50: Lethal Concentration which is lethal to 50% of the population.

LD 50: Lethal Dose which is lethal to 50% of the population.

N/A: Not applicable.

N/AV: Not available.

N/D: Not determined.

OSHA: US Occupational Safety and Health Administration, US Department of Labor.

PEL: Permissible Exposure Limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

Prepared by: CompleteSDS

Approved by: Steve Bishyk, N.A.K.P. Foto Inc.